
Abrasive screen, self-fastening, waterproof

AN 400







Properties

Bonding agent	Resin
Grain	Aluminium oxide
Backing	Polyester screen

Product benefit

Effective and full-surface dust extraction thanks to open grid structure - Dust-free grinding extends the service life of the abrasive - At the same time, improved health and safety thanks to reduced dust formation at the work station - Independent of existing extraction hole patterns - Waterproof

Materials

Paint/Varnish/Filler	●
Gel coats	●
Plaster	●
Plasterboard walls	●
Composite materials	●
Wood	●
Wood-based materials	●

Applications

- Drywall installations
- Paint shops
- Automotive industry
- Boat and shipbuilding
- Wind energy industry
- Wood processing industry

Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter in mm	grain	Hole pattern	Packing unit/pcs.	Cat. number
125	80	Screen	50	337898
125	100	Screen	50	337899
125	120	Screen	50	337900
125	150	Screen	50	337901
125	180	Screen	50	337905
125	240	Screen	50	337904
125	320	Screen	50	337903
125	400	Screen	50	337902
125	600	Screen	50	340402
150	80	Screen	50	337886
150	100	Screen	50	337887
150	120	Screen	50	337885
150	150	Screen	50	337884
150	180	Screen	50	337883
150	220	Screen	50	342146
150	240	Screen	50	337888
150	320	Screen	50	337876
150	400	Screen	50	337877
150	600	Screen	50	340193
225	80	Screen	25	337871
225	100	Screen	25	337875
225	120	Screen	25	337873
225	150	Screen	25	337874
225	180	Screen	25	337872
225	240	Screen	25	337878
225	320	Screen	25	337879
225	400	Screen	25	337880

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de