
Abrasive paper, self-fastening

PS 33 BK





Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Semi-open
Backing	B-paper

Materials

Paint/Varnish/Filler	●
Wood	●
Plastic	◑

Product benefit

Improved abrasive and stock removal performance thanks to special heat-tempered aluminium oxide abrasive grain - Reduced clogging thanks to sanding active fillers in the size coat and the semi-open coating - Outstanding flexibility paired with good stability and tear resistance thanks to latex impregnated paper backing

Applications

- Automotive industry
- Wind energy industry
- Aircraft construction
- Wood processing industry
- Craftsman companies

Available grits:

16 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Width x Length in mm	grain	Hole pattern	type of coat.abras.	Packing unit/pcs.	Cat. number
98 x 148	150	GLS 24	PS 33 BK	100	215477
98 x 148	180	GLS 24	PS 33 BK	100	215478
98 x 148	220	GLS 24	PS 33 BK	100	215479
98 x 148	240	GLS 24	PS 33 BK	100	215480
98 x 148	320	GLS 24	PS 33 BK	100	215482

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de