


Abrasive cloth, multibond

CS 410 X



Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Close
Backing	X-cotton

Product benefit

Cool grinding and no heat tinting due to additional multibond -
Increased abrasive performance for use on stainless steel

Materials

Stainless steel	●
NF metals	○

Applications

- ▶ Apparatus and container manufacturing
- ▶ Railing construction
- ▶ Stainless steel processing industry

Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------

Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
50 x 450	60	F4G butt joint	CS 410 X	25	53108
50 x 450	80	F4G butt joint	CS 410 X	25	53267
50 x 450	120	F4G butt joint	CS 410 X	25	53538

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

