

Abrasive cloth

CS 710 XF



Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Close
Backing	XF-cotton

Product benefit

Machine grinding of molded parts and weld seams in trade and industry - Flexible, yet tear-resistant backing - Abrasive belt with hardened and tempered aluminium oxide

Materials

Steel	●
Stainless steel	●
NF metals	●

Applications

- Metal construction
- Railing construction
- Apparatus and container manufacturing

Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------

Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
9 x 533	80	F4G butt joint	CS 710 XF	25	342297
9 x 533	120	F4G butt joint	CS 710 XF	25	342296
10 x 330	80	F4G butt joint	CS 710 XF	25	342302
10 x 330	120	F4G butt joint	CS 710 XF	25	342303
13 x 455	80	F4G butt joint	CS 710 XF	25	342298
13 x 455	120	F4G butt joint	CS 710 XF	25	342299

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

