Cutting-off wheel

A 930 N *SPECIAL*





Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□
Aggression	■■■■■■
Service life	■■■■■■

Materials

Steel	●
Stainless steel	◑
Aluminium	◑
Castings	◑

Product benefit

Ultimate aggression and service life for universal use (pipes, profiles, solid material) - Low thermal load and minimum burr formation due to one glass fibre reinforcement mesh - An exceptional choice for 110 volt machines and the cutting of solid material

Applications

- Plant engineering
- Apparatus and container manufacturing
- Locksmith's shop
- Steel construction
- Road building
- Construction above and below ground

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
300 x 2,5 x 25,4	▬▬	80 m/s	5100 rpm	10	322627
350 x 3 x 25,4	▬▬	80 m/s	4400 rpm	10	322628

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de